



VALVES

Flow Control Valves

BiS offer a comprehensive range of stainless steel shut-off and metering valves for use on a wide range of operating media. The range includes shut-off valves intended for leak tight isolation and metering valves for flow speed control, with and without reverse flow check functions. Designs are available up to 1,379 bar (20,000 psi), with a large number of installation options, including in-line, ported and cartridge style valves. New to the range, shut-off valves are now available in configurations that match industry standard porting layouts for medium pressure valves.



Contacts

BiS VALVES LTD

Unit 17 - 23, Kingfisher Park, West Moors, Wimborne, Dorset, BH21 6US, UK

Tel No: +44 (0) 1202 896322

Email: salesadmin@bisvalves.co.uk

Fax No: +44 (0) 1202 896718

Web: www.bisvalves.co.uk

Global Distributors

See www.bisvalves.co.uk for contact details



PALM
Tecnologia em Alta Pressão

☎ +55 21 2518-2555

☎ +55 21 99972-3948

✉ admin@palmtecnologia.com.br

🌐 www.palmtecnologia.com.br



www.bisvalves.co.uk

	Nominal Size	Max Pressure*		Valve Type
Shut-Off Valves	1/8"	1,379 bar	(20,000 psi)	BNV10
	1/4"	862 bar	(12,500 psi)	BNV25
	3/8"	862 bar	(12,500 psi)	BNV25/37
	1/4"***	1,379 bar	(20,000 psi)	BNV44AE
	3/8"***	1,379 bar	(20,000 psi)	BNV56AE
	9/16"***	1,379 bar	(20,000 psi)	BNV81AE
Metering Valves	1/8"	552 bar	(8,000 psi)	VFMF25/12
	1/4"	552 bar	(8,000 psi)	VFMF25
	1/4"	552 bar	(8,000 psi)	FMF25
	1/4"	552 bar	(8,000 psi)	MF25
	3/8"	552 bar	(8,000 psi)	MF37
	1/2"	552 bar	(8,000 psi)	MF50
	3/4"	552 bar	(8,000 psi)	MF75
	1"	552 bar	(8,000 psi)	MF100
Metering with Check (micrometer adjustment)	1/4"	552 bar	(8,000 psi)	CMF25
	3/8"	552 bar	(8,000 psi)	CMF37
	1/2"	414 bar	(6,000 psi)	CMF50
	3/4"	414 bar	(6,000 psi)	CMF75
Metering with Check (barrel adjustment)	1"	414 bar	(6,000 psi)	CMF100
	1/4"	552 bar	(8,000 psi)	IMC25
	3/8"	552 bar	(8,000 psi)	IMC37
Pressure Compensated Flow Control Valves	1/2"	552 bar	(8,000 psi)	IMC50
	3/8"	690 bar	(10,000 psi)	PCFR50/37
	1/2"	690 bar	(10,000 psi)	PCFR50

Flow Control Valves

Shut-off Valves

- Stainless steel construction for use with a wide range of operating media
- Non-Rotating Stem Design to reduce seat galling
- Elastomeric stem seals eliminate need to tighten glands
- Available with in-line ports, cartridge style for manifold installation, and with industry standard port layouts to suit medium pressure tubing applications

Metering Valves

- Micrometer or barrel style adjustment for accurate flow control
- Very fine (VFMF) and fine (FMF) metering control options
- Models available with integral check valve for uni-directional metering
- Pressure compensated models provide constant flow with variable pressure differentials

